

FCC Test Report

Report No.: AGC02550250302FE01

FCC ID XBPUV-K1

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Two Way Radio

BRAND NAME : QUANSHENG

UV-K1, UV-K1s, UV-K1(2), UV-K1(5), UV-K1(6), UV-K1(8),

MODEL NAME : UV-K1(9), UV-K1(11), UV-K1(22), UV-K1(55), UV-K1(66),

UV-K1(88), UV-K1(99)

APPLICANT: QUANSHENG ELECTRONICS CO., LTD.

DATE OF ISSUE : May 13, 2025

STANDARD(S) : FCC Part 15 Subpart B

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 35

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 13, 2025	Valid	Initial Release



Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Auxiliary Surrounding Description	5
2.2 Test Methodology	6
2.3 Description of Test Modes	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Used	9
4. Summary of Test Results	10
5. Radiated Emission Measurements	11
5.1 Provisions Applicable	11
5.2 Measurement Setup	11
5.3 Measurement Procedure	12
5.4 Measurement Result	13
6. Conducted Emission Measurements	21
6.1 Provisions Applicable	21
6.2 Measurement Setup	21
6.3 Measurement Procedure	22
6.4 Measurement Result	23
7. Antenna Conducted Power for Receivers	27
7.1 Provisions Applicable	27
7.2 Measurement Setup	27
7.3 Measurement Procedure	27
7.4 Measurement Result	28
8. Scanning Receivers and Frequency Converters Used with Scanning Receivers	32
8.1 Provisions Applicable	32
8.2 Measurement Setup	32
8.3 Measurement Procedure	32
8.4 Measurement Result	33
Appendix I: Photographs of Test Setup	34
Appendix II: Photographs of Test EUT	34



1. General Information

Applicant	QUANSHENG ELECTRONICS CO., LTD.
Address	No 82, Qiuzhong Industry Area Xiamei Town, Nanan City Fujian Province China
Manufacturer	QUANSHENG ELECTRONICS CO., LTD.
Address	No 82, Qiuzhong Industry Area Xiamei Town, Nanan City Fujian Province China
Factory	QUANSHENG ELECTRONICS CO., LTD.
Address	No 82, Qiuzhong Industry Area Xiamei Town, Nanan City Fujian Province China
Product Designation	Two Way Radio
Brand Name	QUANSHENG
Test Model	UV-K1
Series Model(s)	UV-K1s, UV-K1(2), UV-K1(5), UV-K1(6), UV-K1(8), UV-K1(9), UV-K1(11), UV-K1(22), UV-K1(55), UV-K1(66), UV-K1(88), UV-K1(99)
Difference Description	Series models and main model product are only different appearance lines and model names are different.
Date of receipt of test item	Mar. 14, 2025
Date of Test	Apr. 07, 2025~Apr. 19, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCTR-ER-FCC-CSR-V1.0

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Jouk Gai	
	Jack Gui (Project Engineer)	May 13, 2025
Reviewed By	Bibo zhang	
	Bibo Zhang (Reviewer)	May 13, 2025
Approved By	Angole li	
	Angela Li (Authorized Officer)	May 13, 2025



Page 5 of 35

2. Product Information

2.1 Product Technical Description

Housing Type	Plastic and metal
Receive Frequency Range	50-76MHz, 108-600MHz (Scanning Receiver)
Highest Operating Frequency	⊠Greater than 108MHz □Less than 108MHz
Equipment Type	Table-Top
Hardware Version	K1-V1.0
Software Version	V6.00.06
Power Supply	DC 12V from Adapter and DC 7.4V, 1400mAh by Battery or DC 12V from Adapter and DC 7.4V, 2500mAh by Battery

I/O Port Information (⊠Applicable □Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Antenna Port	1	0	1
Type-C Port	1	0	1
Earphone Port	1	0	1

2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

☐ Test Accessories Come From The Laboratory

N	ο.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	1	Adapter	XIAOMI	MDY-11-EF	Input(AC):100V-240V 50/60Hz, 0.7A Output: DC 12V 2.5A	2.2m,unshiel ded

☐ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Battery1#	QUANSHENG ELECTRONICS CO., LTD.	BP9614SD	DC 7.4V 1400mAh	
2	Battery2#	QUANSHENG ELECTRONICS CO., LTD.	BP6828SG	DC 7.4V 2500mAh	
3	Charger	N/A	C-51	Input: DC 12V 1A Output: 8.4V 0.5A	



Page 6 of 35

2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.3 Description of Test Modes

No.	Test Mode	Remark
1	Scanning mode	Worst
2	Scanning stopped/Receiving at low channel of 50 MHz to 76 MHz	
3	Scanning stopped/Receiving at middle channel of 50 MHz to 76 MHz	
4	Scanning stopped/Receiving at high channel of 50 MHz to 76 MHz	
5	Scanning stopped/Receiving at low channel of 108 MHz to 600 MHz	
6	Scanning stopped/Receiving at middle channel of 108 MHz to 600 MHz	
7	Scanning stopped/Receiving at high channel of 108 MHz to 600 MHz	

Note: Only the result of the worst case was recorded in the report.



Page 7 of 35

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 35


3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$





3.5 List of Equipment Used

•	Radiated Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2025-01-14	2026-01-13		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23		
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10		
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2025-03-29	2026-03-28		
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23		

•	AC Power Line Conducted Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23		
\boxtimes	AGC-ER-A007	6dB Fixed Attenuator	Mini circuits	BW-S6-2W263 A+	N/A	2025-01-30	2026-01-29		
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		

• Tes	Test Software									
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information					
\boxtimes	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0					
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A					
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71					



Page 10 of 35

4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	Pass
3	§15.111	Antenna Conducted Power for Receivers	/	Pass
4	§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	/	Pass




5. Radiated Emission Measurements

5.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
ADOVE IGHZ	74.00	80.00	Peak

5.2 Measurement Setup



Radiated Emission Measurements Test Setup for 30MHz to 1GHz



Radiated Emission Measurements Test Setup for above 1GHz



Page 12 of 35

5.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the guasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.


EMI Test Receiver Setup:

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Abovo 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.




5.4 Measurement Result




Final I	Final Data List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	34.85	31.56	11.83	40.00	8.44	100	138	Horizontal	
2	54.25	28.78	16.35	40.00	11.22	100	341	Horizontal	
3	109.54	30.43	16.58	43.50	13.07	100	254	Horizontal	
4	141.55	30.06	16.13	43.50	13.44	100	180	Horizontal	
5	616.85	31.01	25.58	46.00	14.99	100	229	Horizontal	
6	844.8	35.45	29.48	46.00	10.55	100	97	Horizontal	

RESULT: PASS









Final I	Final Data List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	30.97	34.43	13.01	40.00	5.57	100	235	Vertical	
2	62.01	31.68	17.23	40.00	8.32	100	56	Vertical	
3	101.78	34.27	16.98	43.50	9.23	100	202	Vertical	
4	460.68	29.36	24.60	46.00	16.64	100	152	Vertical	
5	625.58	30.97	25.12	46.00	15.03	100	231	Vertical	
6	862.26	37.24	29.93	46.00	8.76	100	276	Vertical	

RESULT: PASS








Final Data List Freq. Level Factor Limit Margin Height Angle NO. **Polarity** [dB] [dB] [MHz] [dBµV/m] [dBµV/m] [cm] 1 1234.046809 33.72 -17.96 74.00 40.28 100 150 Horizontal 39.95 2 1565.113023 34.05 -17.01 74.00 100 Horizontal 20 3 2068.213643 38.07 -13.2574.00 35.93 100 40 Horizontal 4 2908.381676 37.51 -12.02 74.00 100 150 36.49 Horizontal 40.80 74.00 100 230 5 4319.663933 -8.63 33.20 Horizontal 44.39 74.00 100 6 5871.974395 -5.78 29.61 350 Horizontal

RESULT: PASS





74.00

74.00

74.00

74.00

34.62

35.80

32.70

31.07

100

100

100

100

60

0

320

300

Vertical

Vertical

Vertical

Vertical

RESULT: PASS

2309.261852

3400.480096

4368.673735

5657.931586

39.38

38.20

41.30

42.93

-12.66

-10.91

-8.43


-6.41

3


4

5

6







40.00

43.50

43.50

46.00

46.00

10.76

13.26

12.04

15.17

10.38

100

100

100

100

100

6

130

2

126

101

Horizontal

Horizontal

Horizontal

Horizontal

Horizontal

RESULT: PASS

54.25

110.51

141.55

619.76

901.06

29.24

30.24

31.46

30.83

35.62

16.35

16.50

16.13

25.90

29.99


2

3


4

5

6









Final I	Final Data List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	34.85	33.51	11.83	40.00	6.49	100	357	Vertical	
2	68.8	31.37	15.04	40.00	8.63	100	97	Vertical	
3	100.81	34.45	17.04	43.50	9.05	100	146	Vertical	
4	141.55	31.66	16.13	43.50	11.84	100	101	Vertical	
5	620.73	30.89	25.82	46.00	15.11	100	67	Vertical	
6	868.08	35.41	29.74	46.00	10.59	100	359	Vertical	

RESULT: PASS








Final	Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1321.064213	33.75	-17.83	74.00	40.25	100	230	Horizontal
2	1667.133427	35.32	-16.16	74.00	38.68	100	350	Horizontal
3	2153.230646	38.29	-13.03	74.00	35.71	100	320	Horizontal
4	2890.378076	37.72	-12.02	74.00	36.28	100	310	Horizontal
5	4235.647129	40.76	-8.99	74.00	33.24	100	50	Horizontal
6	5591.918384	42.52	-6.61	74.00	31.48	100	310	Horizontal

RESULT: PASS





74.00

30.98

100

140

Vertical

RESULT: PASS

5663.932787

Note:

6

1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Measurement.

-6.40

2. The "Factor" value can be calculated automatically by software of measurement system.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

43.02



6. Conducted Emission Measurements

6.1 Provisions Applicable

FCC CFR Title 47 Part 15 Subpart B Section 15.107:


For Class B Limits:

Fraguenay	Maximum RF Line Voltage				
Frequency	Q.P. (dBμV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

For Class A Limits:

Fraguenay	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	79	66			
500kHz~30MHz	73	60			

6.2 Measurement Setup





Page 22 of 35

6.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipment received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test data of the worst case condition (Mode 1) was reported on the following Data page.



6.4 Measurement Result

Mode	de Mode 1(DC 12V from Adapter and DC 7.4V, 1400mAh by Battery) LISN Line Hot Side																		
Leve	el [dBµ	V]			,	,,			,			-,	-,		,-	-			
70 60	 			<u> </u>	¦	 			¦ !			-¦ -!	-¦ ·			+ - 			
50 40 V	~~/\	M-M	/ ³	ν _ν ν	~-		L.				الباس		y dig		केल ज	+	description,		
30 20	~~^	wy	~	~	<u>, </u>	~**\ <u>~</u>	; ; ; ; ; ;		-	ے اوال سرور اور میں میں میں	المعلقية المعادمة	-	-			7 4 3 F	Tall Control of the last		
10 0	·				 	' ' 	1 — L . 1 — I 1 — F -		¦ ¦	 	 	-¦ - !	- · - ·	1 - J 1 - J 1 - J		+ -! ! !			
	0k	30	0k 400)k	600k	800k	1M		2M equenc	31 v [Hz]	M 4	1M	5M 6	M	8M	10M		20M	30M

MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.398000 4.030000 4.434000 4.606000 4.990000 5.754000	42.90 35.00 36.90 36.30 35.70 37.40	6.1 6.3 6.3 6.3 6.4	58 56 56 56 56	15.0 21.0 19.1 19.7 20.3 22.6	QP QP QP QP QP OP	L1 L1 L1 L1 L1

MEASUREMENT RESULT: "agc_fin2"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.398000 0.638000 0.766000 0.954000 4.490000 5.790000	36.00 26.80 26.60 25.50 28.90 29.70	6.1 6.2 6.2 6.2 6.3 6.4	48 46 46 46 46	11.9 19.2 19.4 20.5 17.1 20.3	AV AV AV AV AV	L1 L1 L1 L1 L1

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.418000 3.458000	40.20 31.20	6.1 6.3	58 56	17.3 24.8	ÕР	N N
3.526000	31.40	6.3	56	24.6	~	N
3.890000	33.20	6.3	56	22.8	QP	N
4.450000	34.60	6.3	56	21.4	QP	N
5.666000	35.00	6.4	60	25.0	QP	N

MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.254000	29.00	6.1	52	22.6	VA	N
0.362000	28.50	6.1	49	20.2	VA	N
0.410000	36.50	6.1	48	11.1	VA	N
0.954000	24.10	6.2	46	21.9	VA	N
4.246000	28.40	6.3	46	17.6	AV	N
5.246000	28.60	6.4	50	21.4	AV	N

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



t Mode		ode 1 4V, 25								apter and	DC	LISN	l Lir	ne				Hot S	ide	
Leve	el [dB _l	μV]																		
80 -						<u>-</u> -	<u>:</u>					;	;				T-1-1			
70	<u>-</u> -		<u></u>		<u> </u>	 	 	- + -	- - -			¦	 	¦			+			
60	L		<u> </u>	<u></u>	<u>i</u>	i_	<u> </u>		<u> </u>			i	i			÷	i i		<u> </u>	
50	-		<u> </u>	- <u>-</u>	<u>-</u>	 		- +-	- ¦			\	¦		i	÷	 		<u>i</u>	
40	4.	M*/~~	/-	<u>^\&.^\</u>	 	L	 	 + -		samos a acc		1 1 – – Jane	e de la		1	l Handrid	l I Manadara			ا ا- حدد
30	<u>₩</u>		<u>'w</u>	<u>^</u> ~~	<u> </u>	mr.	n _e	1	1	A STATE OF THE PARTY OF THE PAR	AND DESCRIPTION OF THE PERSON		XXX	, ^				and the state of	diameter (
20	\sim	$\sim \sim$	\\\\	-	my	w	فعمماه	A HOPE	May.	And spirit with the same and	and the second	and or other Designations	1	i						
			!	 !		!			-			!		 			+-!			
10 -					†	;			- - -				;		1		† -;- :			
0 -	i		<u></u> -		÷	i	<u>-</u> -i		· ·			i	i		i	j-	÷ -i		·j	
-10	0k	20	i 00k 4	00k	i er)0k	00	Ok.	184	. 2	M 2	і М 4	M 5	М 6	i i	OM	10M		20M	30M
15	OUK	30	JUK 4	OUK	00	JUK	00	UK	HVI		vi 3 ency [Hz]	IVI 4	ivi 5	IVI O	IVI	OIVI	TOW		ZUIVI	JUIVI

MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.406000	42.70	6.1	58	15.0	~	L1
0.474000	40.50	6.1	56	15.9	QP	L1
4.098000	36.40	6.3	56	19.6	QP	L1
4.382000	37.40	6.3	56	18.6	QP	L1
4.726000	37.30	6.3	56	18.7	QP	L1
5.846000	38.40	6.4	60	21.6	QP	L1

MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.402000 0.658000 0.798000 0.958000 4.690000 5.582000	36.00 26.60 26.70 26.00 29.90 30.70	6.1 6.2 6.2 6.3 6.4	48 46 46 46 46 50	11.8 19.4 19.3 20.0 16.1 19.3	AV AV AV AV AV	L1 L1 L1 L1 L1

RESULT: PASS



	Ac Power Line Conducted Emission Test																		
est Mode		ode 4V, 2							apter and	DC	LISN	l Lir	ie				Neutra	al Sid	de
Lev	el [dB	μV]																	
80 -					 	:										 - -			
70 <u>-</u> 60 -			-F		L	 	- -	7 - T		 		-ı ! -l		Ţ — —	1 	T - -			
50 -			-		 			 			-	-¦				11		-	
40 🗠	Mųį	7√\ <u>₩</u> .	- <u>L</u>	Υ <u>τ΄</u> χ	<u>-</u> -	 -	-	 	. 10 . 11	i I	1	a della			i Landa	i i	hallana .		
30 -		~/\	<u>~'!\/~</u>	ريب	<u>/~\v</u>	/~\ 	<u>\po(\</u>	4	Marithania Maritania	Apple Delication	x	XX	-			Ţ÷,	and the latest and the same	e Leistelle Leistelle	-
20	<u> </u>		- -		ř-~	i	Ϋ́	7-1	A STATE STATE OF STREET STATE OF STATE	i	- -	-i			i i -	+ - -	The state of the s		
10 -	¦				<u> </u>	!! !	¦-	1-1		' '		-	 	<u> </u>	<u> </u>	+			
10					+ ! <u>!</u>	 		7 - † ! !		 	-	- 	 	1 – – !	11- 	- -			
	50k	3	800k 4	100k	60	0k	8001	k 11		M ency [Hz		IM 5	M 6	М	8M	101	И	20M	30M
x x x1	MES	agc_fi	in																

MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.458000	40.60	6.1	57	16.1	QP	N
3.422000	31.50	6.3	56	24.5	QP	N
4.198000	34.80	6.3	56	21.2	QP	N
4.422000	35.60	6.3	56	20.4	QP	N
4.502000	36.10	6.3	56	19.9	QP	N
5.486000	36.20	6.4	60	23.8	OP	N


MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.262000 0.410000 0.806000 0.982000 4.554000 5.934000	29.60 37.30 26.40 24.70 30.10 29.30	6.1 6.2 6.2 6.3 6.4	51 48 46 46 46 50	10.3 19.6	AV AV AV AV AV	N N N N N

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






7. Antenna Conducted Power for Receivers

7.1 Provisions Applicable

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz
Limit	2.0 nW (-57 dBm)

7.2 Measurement Setup




7.3 Measurement Procedure

- 1. The receiver antenna terminal connected to a spectrum analyzer.
- 2. Receiver set as follow:

Frequency range	RBW (kHz)	VBW (kHz)	
9 kHz ~ 150 kHz	1	3	
150 kHz ~ 30 MHz	10	30	
30 MHz ~ 1000 MHz	100	300	
1000 MHz ~ 3000 MHz	1000	3000	

3. The test data of the worst case condition (mode 1) was reported on the following Data page.







7.4 Measurement Result

For Battery1#:

Test Graphs of Antenna Conducted Power for Receivers








RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






For Battery2#:










RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






8. Scanning Receivers and Frequency Converters Used with Scanning Receivers

8.1 Provisions Applicable

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

8.2 Measurement Setup



8.3 Measurement Procedure

- 1) Connected the EUT as shown in the above block diagram.
- Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
- 3) Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
- 4) Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB. This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
- 5) Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
- 6) Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5) and its frequency to the frequency points in the cellular band.
- 7) Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
- 8) Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
- 9) If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
- 10) Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.



Page 33 of 35

8.4 Measurement Result

Scanning Frequency Band (MHz)	Test Frequency of Cellular Band (MHz)	Spurious Value of Cellular Frequency (dBm)	Reference Sensitivity (dBm)	Measurement Result (dB)	Limit (dB)
108-600	824.5/836.0/848.5	>-44	-107	<-63	<-38
108-600	869.1/881.5/893.5	>-44	-107	<-63	<-38

Note:

- Measurement Result = Rejection Ratio
- 2. Reference Sensitivity is the recorded value when the signal-to-noise ratio is 12dB.
- 3. Measurement Result = Reference Sensitivity- Spurious Value.
- 4. Since the scanning operating frequency is 50-76MHz, the influence of the public mobile frequency band cannot be received, so it is ignored and not evaluated.



Page 34 of 35

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC02550250302AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC02550250302AP03



Page 35 of 35

Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

 3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations. 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

